



SPECIFICATION:

SPECIFY THE LIGHTING STATION ABOVE THE BATHROOM VANITY. THE TOP OF THE FIXTURE SHOULD BE A MINIMUM OF 6'6" OFF THE FINISHED FLOOR TO ACCOMMODATE THE HEIGHT OF A HOTEL GUEST.

THE MC CABLE IS BROUGHT IN THROUGH THE CHASSIS KNOCKOUT AND CONNECTED TO TERMINAL CONNECTOR. NO ELECTRICAL BOX REQUIRED. ELECTRICAL POWER SHOULD BE CONTROLLED BY A LIGHT SWITCH. 120 OR 240 VOLT VERSIONS.

FIXTURE SHOULD BE MOUNTED TO A MECHANICALLY SOUND SURFACE SUCH AS WALL STUDS TO SUPPORT ITS WEIGHT. MOUNTING HOLES ARE PROVIDED IN THE CHASSIS.

POWER REQUIREMENTS:

120 VOLTS, .9 AMPS

LAMP SPECIFICATION:

NOMINAL LENGTH (in): 48
 NOMINAL WATTAGE: 54
 BULB: 2 X T5
 AVG RATED LIFE (hrs): 20000
 CCT (K): 3000
 LUMENS: 4200
 CRI: 82

LAMP SPECIFICATION:

NOMINAL LENGTH (in): 60
 NOMINAL WATTAGE: 80
 BULB: 2 X T5
 AVG RATED LIFE (hrs): 20000
 CCT (K): 3000
 LUMENS: 5800
 CRI: 82

	NAME	DATE	ELECTRIC MIRROR, LLC © 2007	
DRAWN BY:	SY	4/19/07	TITLE:	
CHECKED BY:			EMBRACE-81.00X55.00	
PROJECT:			SIZE	DWG. NO.
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ELECTRIC MIRROR L.L.C. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ELECTRIC MIRROR L.L.C. IS PROHIBITED. COPYRIGHT 2007.			A	WEB SPEC
				REV
			A	
DIMS IN INCHES		SCALE: 1:24	SHEET 1 OF 1	