



**SPECIFICATION:**

SPECIFY THE LIGHTING STATION ABOVE THE BATHROOM VANITY. THE TOP OF THE FIXTURE SHOULD BE A MINIMUM OF 6'6" OFF THE FINISHED FLOOR TO ACCOMMODATE THE HEIGHT OF A HOTEL GUEST.

THE MC CABLE IS BROUGHT IN THROUGH THE CHASSIS KNOCKOUT AND CONNECTED TO TERMINAL CONNECTOR. NO ELECTRICAL BOX REQUIRED. ELECTRICAL POWER SHOULD BE CONTROLLED BY A LIGHT SWITCH. 120 OR 240 VOLT VERSIONS.

FIXTURE SHOULD BE MOUNTED TO A MECHANICALLY SOUND SURFACE SUCH AS WALL STUDS TO SUPPORT ITS WEIGHT. MOUNTING HOLES ARE PROVIDED IN THE CHASSIS.

**POWER REQUIREMENTS:**

**LAMPS SPECIFICATIONS:**

36" (2 X T5)  
 NOMINAL WATTAGE: 39  
 AVG RATED LIFE (hrs): 20000  
 CCT (K): 3000  
 LUMENS: 3100  
 CRI: 82

24" (2 X T5)  
 NOMINAL WATTAGE: 24  
 AVG RATED LIFE (hrs): 20000  
 CCT (K): 3000  
 LUMENS: 1750  
 CRI: 82

	NAME	DATE	<b>ELECTRIC MIRROR, LLC © 2006</b>	
DRAWN BY:	WF	8-28-06	TITLE:	
CHECKED BY:	PDE	8-28-06	<b>INTEGRITY-37.00X37.00</b>	
PROJECT:			SIZE	DWG. NO.
<b>PROPRIETARY AND CONFIDENTIAL</b> <small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ELECTRIC MIRROR L.L.C. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ELECTRIC MIRROR L.L.C. IS PROHIBITED. COPYRIGHT 2006.</small>			<b>A</b>	<b>WEB SPEC</b>
			REV	<b>A</b>
DIMS IN INCHES		SCALE: 1:16	SHEET 1 OF 1	

120 VOLTS, 1.0

**AMP**