



ISOMETRIC VIEW

SPECIFICATION:

SPECIFY THE LIGHTING STATION ABOVE THE BATHROOM VANITY. THE TOP OF THE FIXTURE SHOULD BE A MINIMUM OF 6'6" OFF THE FINISHED FLOOR TO ACCOMMODATE THE HEIGHT OF A HOTEL GUEST.

THE MC CABLE IS BROUGHT IN THROUGH THE CHASSIS KNOCKOUT AND CONNECTED TO TERMINAL CONNECTOR. NO ELECTRICAL BOX REQUIRED. ELECTRICAL POWER SHOULD BE CONTROLLED BY A LIGHT SWITCH. 120 OR 240 VOLT VERSIONS.

FIXTURE SHOULD BE MOUNTED TO A MECHANICALLY SOUND SURFACE SUCH AS WALL STUDS TO SUPPORT ITS WEIGHT. MOUNTING HOLES ARE PROVIDED IN THE CHASSIS.

LAMP SPECIFICATION:

NOMINAL WATTAGE: 55
 BULB: CIRCLINE T5
 OUTSIDE DIAMETER (in): 12
 AVG RATED LIFE (hrs): 12000
 CCT (K): 3000
 LUMENS: 3200
 CRI: 82

	NAME	DATE	ELECTRIC MIRROR, LLC	
DRAWN	PDE	11-9-05	TITLE:	
CHECKED			TRINITY-21.00X30.00	
PROJECT:			SIZE	DWG. NO.
<small>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ELECTRIC MIRROR L.L.C. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ELECTRIC MIRROR L.L.C. IS PROHIBITED. COPYRIGHT 2005.</small>			B	SPEC SHEET
				REV
			SCALE: 1:8	SHEET 1 OF 1