



### PRODUCT DESCRIPTION

Combining a timeless, balanced shape with inward-facing directional lighting is sheer Brilliance™. The front-lit design of this modern, slim-profile mirror elevates task lighting to a level never before seen.

### SPECIFICATION STATEMENT

Solution shall consist of a round or oval lighted mirror with LEDs mounted in a 45° channel in the frame of the mirror, with inward-facing directional lighting on the front face of the mirror and ambient wall glow behind the mirror. LEDs will be covered by an integrated diffuser and shall have an L<sub>70</sub> calculated life of 36,000 hours, with a greater than or equal to 90 CRI (color rendering index). Product shall incorporate a driver enclosure that is to be mounted to the back of the mirror. Product will have a 10-year limited warranty.

### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

### FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Inward-facing task lighting for brilliant facial illumination
- Wall-glow ambient lighting with diffuser for a finished side view
- Greater illuminance with half the power consumption of traditional LED mirrors
- 0-10V dimming
- Sleek and modern profile
- Matte black finish
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Easy installation
- Title 24 compliance available
- 10-year limited warranty
- Patent pending
- Designed in America and sourced globally

### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 252 lumens per foot (front light)
- 468 lumens per foot (wall glow)
- Maximum 100 lumens per watt efficacy
- Calculated L<sub>70</sub> 36,000-hour LED lifespan
- Built-in EMX diffusers

### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror

## INSTALLATION SPECIFICATIONS

- 120V hardwire electrical connection; junction box required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by non-dimming wall switch for on/off, or 0-10V dimming wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

## MODELS

Base Model*	Dimensions	Power Requirements
BRI3-30.00-01L-D1-OS-WG3-30K	30" diameter x 2.13"D (762mm x 54mm)	120V, 71W
BRI3-36.00-01L-D1-OS-WG3-30K	36" diameter x 2.13"D (914mm x 54mm)	120V, 84W
BRI3-24.00X36.00-01L-D1-OS-WG3-30K	24.00"W x 36.00"H x 2.13"D (610mm x 914mm x 54mm)	120V, 71W

\*Base model number shown only. To specify additional options, contact Electric Mirror at [sales@electricmirror.com](mailto:sales@electricmirror.com).

## DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

