



PRODUCT DESCRIPTION

The Crown™ is a stately new addition to Electric Mirror's collection of lighted mirrors. Featuring a raised mirrored surface with a refined 1" beveled edge bordered by a halo of luxurious light, the Crown distinguishes any space with grace and grandeur.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with a 4mm raised mirror surface with a 1" beveled edge. Mirror must provide forward-facing task lighting as well as wall-glow ambient lighting around the mirror. Mirror shall have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Raised mirror surface for multi-dimensional effect
- 1" beveled edge on raised mirror surface for added elegance
- Copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting with diffuser for a finished side view
- Environmentally sustainable
- Energy efficient
- Easy installation
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

AVAILABLE OPTIONS

- Forward-phase dimming¹
- 2,700K CCT¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 869 lumens per foot
- Calculated L₇₀ 52,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications

¹ Minimum order quantity required.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options

MODELS

Base Model*	Dimensions	Power Requirements
CRO2-21.00x30.00-BV1.0-L7H-30K	21"W x 30"H x 2.07"D (Oval) (533mm x 762mm x 53mm)	120/240 VAC, 46W
CRO2-30.00- BV1.0-L7H-30K	30" diameter x 2.07"D (762mm x 53mm)	120/240 VAC, 57W
CRO2-36.00- BV1.0-L7H-30K	36" diameter x 2.07"D (914mm x 53mm)	120/240 VAC, 72W

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

