



#### PRODUCT DESCRIPTION

The Prism™ is a stunning new addition to Electric Mirror's collection of lighted mirrors. Showcasing a raised mirrored surface with an exquisite 1" beveled edge bordered by an inset band of resplendent light, the Prism creates a spectacular centerpiece for any room.

#### SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with a 4mm raised mirror surface with a 1" beveled edge. Mirror must provide forward-facing task lighting and have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

#### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

#### FEATURES AND BENEFITS

- Raised mirror surface for multi-dimensional effect
- 1" beveled edge on raised mirror surface for added elegance
- Copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Environmentally sustainable
- Energy efficient
- Easy installation
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

#### AVAILABLE OPTIONS

- Forward-phase dimming<sup>1</sup>
- 2,700K CCT<sup>1</sup>

#### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 604 lumens per foot
- Calculated L<sub>70</sub> 124,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

#### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications

<sup>1</sup>Minimum order quantity required.

**INSTALLATION SPECIFICATIONS**

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options

**MODELS**

Base Model*	Dimensions	Power Requirements
PRI2-24.00x36.00-BV1.0-L7CS-30K	24"W x 36"H x 2.07"D (610mm x 914mm x 53mm)	120/240 VAC, 49W
PRI2-36.00x36.00- BV1.0-L7CS-30K	36"W x 36"H x 2.07"D (914mm x 914mm x 53mm)	120/240 VAC, 62W
PRI2-48.00x36.00- BV1.0-L7CS-30K	48"W x 36"H x 2.07"D (1219mm x 914mm x 53mm)	120/240 VAC, 73W
PRI2-60.00x36.00- BV1.0-L7CS-30K	60"W x 36"H x 2.07"D (1524mm x 914mm x 53mm)	120/240 VAC, 88W

\*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

**DIMENSIONAL DRAWING** *(Not to scale.)*

