



PRODUCT DESCRIPTION

The Facet™ is a beautiful new addition to Electric Mirror's collection of lighted mirrors. Featuring a raised mirrored surface with a classic 1" beveled edge juxtaposed against a border of radiant light, the Facet offers a distinctive and stylish focal point for any room.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with a 4mm raised mirror surface with a 1" beveled edge. Mirror must provide forward-facing task lighting as well as wall-glow ambient lighting around the mirror. Mirror shall have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Raised mirror surface for multi-dimensional effect
- 1" beveled edge on raised mirror surface for added elegance
- Copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting with diffuser for a finished side view
- Environmentally sustainable
- Energy efficient
- Easy installation
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

AVAILABLE OPTIONS

- Forward-phase dimming¹
- 2,700K CCT¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 695 lumens per foot
- Calculated L₇₀ 52,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications

¹Minimum order quantity required.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options

MODELS

Base Model*	Dimensions	Power Requirements
FAC2-24.00x36.00-BV1.0-L7CSHD-30K	24"W x 36"H x 2.07"D (610mm x 914mm x 53mm)	120/240 VAC, 67W
FAC2-36.00x36.00- BV1.0-L7CSHD-30K	36"W x 36"H x 2.07"D (914mm x 914mm x 53mm)	120/240 VAC, 85W
FAC2-48.00x36.00- BV1.0-L7CSHD-30K	48"W x 36"H x 2.07"D (1219mm x 914mm x 53mm)	120/240 VAC, 100W
FAC2-60.00x36.00- BV1.0-L7CSHD-30K	60"W x 36"H x 2.07"D (1524mm x 914mm x 53mm)	120/240 VAC, 120W

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale.)

