



PRODUCT DESCRIPTION

Add glimmering light and tasteful grace to any space with a powerful impression of Integrity™. Featuring a smooth polished edge and brilliant inner frame of frosted light, this radiant marvel is as stylish as it is functional.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using dimmable, replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- Title 24 compliant
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

AVAILABLE OPTIONS

- Ava™ SmartLook™ Technology¹
- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Forward-phase, dimmable, replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin (Without Ava)
- CCT: 2,700/4,600/6,500 Kelvin (With Ava)
- 869 lumens per foot
- Calculated L₇₀ 52,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- For Integrity without Ava, fixture can be controlled by an on/off switch or forward-phase dimming switch
- For Integrity with Ava, fixture can be controlled by an on/off switch or by using Ava touch control, located on the mirror 6" up from the bottom border

¹ See technology specification sheets for more information.

MODELS

Base Model	Base Model with Ava	Dimensions	Power Requirements
INT-2436	INT-2436-AE	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	120/240 VAC, 73W
INT-3042	INT-3042-AE	30"W x 42"H x 1.75"D (762mm x 1067mm x 44mm)	120/240 VAC, 93W
INT-3636	INT-3636-AE	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	120/240 VAC, 93W
INT-3642	INT-3642-AE	36"W x 42"H x 1.75"D (914mm x 1067mm x 44mm)	120/240 VAC, 100W
INT-4236	INT-4236-AE	42"W x 36"H x 1.75"D (1067mm x 914mm x 44mm)	120/240 VAC, 100W
INT-4242	INT-4242-AE	42"W x 42"H x 1.75"D (1067mm x 1067mm x 44mm)	120/240 VAC, 109W
INT-4836	INT-4836-AE	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	120/240 VAC, 109W
INT-5442	INT-5442-AE	54"W x 42"H x 1.75"D (1372mm x 1067mm x 44mm)	120/240 VAC, 131W
INT-6036	INT-6036-AE	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	120/240 VAC, 131W
INT-6642	INT-6642-AE	66"W x 42"H x 1.75"D (1676mm x 1067mm x 44mm)	120/240 VAC, 152W

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

