



#### FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting on all four sides with diffuser for a finished side view
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 10-year limited warranty
- Covered by one or more patents
- Made in America with U.S. and global components

#### AVAILABLE OPTIONS

- Ava™ Technology <sup>1,2</sup>
- Keen™ Technology <sup>2</sup>
- Polaris™ Technology <sup>1,2</sup>
- Seamless™ Technology <sup>1,2</sup>
- Vive™ Technology <sup>1,2</sup>
- Defogger
- CCT: 2,700K
- 0-10V dimming
- Forward-phase dimming
- 277V available <sup>3</sup>
- Custom sizes

#### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- Replaceable LEDs
- 720 lumens per foot
- Maximum 100 lumens per watt efficacy
- Calculated L<sub>70</sub> 52,000-hour LED lifespan

#### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

<sup>1</sup> Minimum order quantity required

<sup>2</sup> See technology specification sheets for more details

<sup>3</sup> May not be compatible with all upgrades and options

#### PRODUCT DESCRIPTION

An illusion of free-floating reflection merges seamlessly with resplendent light to create the perfect Silhouette™. With practical task lighting and soft wall glow, this beautiful lighted mirror will illuminate your bathroom in brilliant splendor.

#### SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting as well as wall-glow ambient lighting around the mirror. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 10-year limited warranty.

#### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

**INSTALLATION SPECIFICATIONS**

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

**MODELS**

Base Model*	Dimensions	Power Requirements
SIL2-24.00x36.00-L7CSHD-30K	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	120/240 VAC, 74W
SIL2-30.00x42.00-L7CSHD-30K	30"W x 42"H x 1.75"D (762mm x 1067mm x 44mm)	120/240 VAC, 91W
SIL2-36.00x36.00-L7CSHD-30K	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	120/240 VAC, 93W
SIL2-42.00x42.00-L7CSHD-30K	42"W x 42"H x 1.75"D (1067mm x 1067mm x 44mm)	120/240 VAC, 116W
SIL2-48.00x36.00-L7CSHD-30K	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	120/240 VAC, 115W
SIL2-54.00x42.00-L7CSHD-30K	54"W x 42"H x 1.75"D (1372mm x 1067mm x 44mm)	120/240 VAC, 137W
SIL2-60.00x36.00-L7CSHD-30K	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	120/240 VAC, 132W
SIL2-66.00x42.00-L7CSHD-30K	66"W x 42"H x 2"D (1676mm x 1067mm x 51mm)	120/240 VAC, 157W

\*Base model number shown only. To specify additional options, contact Electric Mirror at [sales@electricmirror.com](mailto:sales@electricmirror.com).

**DIMENSIONAL DRAWING** (Not to scale. Frost and border widths may vary depending on mirror size.)

