

Eyla™ Lighted Mirror

Product Specifications: Residential

ELECTRIC MIRROR®



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting on all four sides with diffuser for a finished side view
- Forward-phase dimming technology
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Keen™ Technology ¹
- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- Replaceable LEDs
- 695 lumens per foot
- Maximum 100 lumens per watt efficacy
- Calculated L₇₀ 52,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ See technology specification sheets for more details

PRODUCT DESCRIPTION

Bring soothing tranquility to any space with the gentle curves and radiant wall glow of the Eyla™. Combining practical task lighting with subdued ambiance, this mirror offers blissful balance for any project.

SPECIFICATION STATEMENT

Solution shall consist of a radius-corner lighted mirror with forward-facing task lighting as well as wall-glow ambient lighting around the mirror. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 7-year limited warranty

THE ELECTRIC MIRROR ADVANTAGE

- ✓ Global mirror technology leader for over 20 years
- ✓ More installations than all competitors combined
- ✓ Realistic warranty you can believe in and trust
- ✓ Lowest total cost of ownership
- ✓ U.S. based customer service support
- ✓ 125,000 square foot American manufacturing facility



INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Keen model controlled by capacitive touch button on fixture or non-dimming on/off wall switch
- Non-Keen model controlled by forward-phase dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model	Base Model with Keen	Dimensions	Power Requirements
EYL-2436	EYL-2436-KG	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	120 or 277 VAC, 75W
EYL-3636	EYL-3636-KG	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	120 or 277 VAC, 94W
EYL-4836	EYL-4836-KG	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	120 or 277 VAC, 114W
EYL-6036	EYL-6036-KG	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	120 or 277 VAC, 133W

*Base model number shown only. To specify additional options, contact Electric Mirror at residential@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

