



PRODUCT DESCRIPTION

Every modern space could use an eye-catching Element™ to emphasize the room's contemporary décor. Secured to the ceiling by a stainless-steel frame and featuring two vertical bands of pure, natural-looking light, this urbane design balances great looks with lasting performance.

SPECIFICATION STATEMENT

Solution shall consist of a stainless steel, ceiling mounted frame, lighted mirror with forward-facing task lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using-replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 10-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Full mirror on reverse side
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- Title 24 compliance available
- 10-year limited warranty
- Patent: www.electricmirror.com/patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Keen™ Technology ^{1, 2}
- Seamless™ Technology ^{1, 2}
- Defogger
- CCT: 2,700K
- 0-10V dimming
- Forward-phase dimming
- 277V available ³
- Polished stainless-steel finish (standard)
- Brushed stainless-steel finish (optional)

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- Replaceable LEDs
- 50 initial lumens/inch
- Maximum 100 lumens/watt efficacy
- Calculated L₇₀ 124,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ Minimum order quantity required

² See technology specification sheets for more details

³ May not be compatible with all upgrades and options

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 12" whip; junction box not required
- Power to fixture supplied with MC cable exiting ceiling and entering through chassis knockout
- Fixture is ceiling mounted either 60" or 72" above countertop; ceiling must be sufficient in strength to handle weight of entire fixture
- Includes multiple ceiling mounting slots and counter mounted anchor
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Assembly Height	Power Requirements
ELE60-24.25x38.38-PS-L7-30K	24.25"W x 38.38"H x 2.75"D (616mm x 975mm x 64mm)	60"H (1524mm)	120/240 VAC, 41W
ELE72-24.25x38.38-PS-L7-30K	24.25"W x 38.38"H x 2.75"D (616mm x 975mm x 64mm)	72"H (1829mm)	120/240 VAC, 41W

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

