



#### PRODUCT DESCRIPTION

Offering natural-looking LED light for the vanity and ceiling, while bathing the room with radiant wall-glow light, the Novo-4™ provides a novel approach to both form and function.

#### SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting as well as top and bottom wall-glow ambient lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using replaceable LEDs with a greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 10-year limited warranty.

#### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

#### FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting on top and bottom with diffuser for a finished side view
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 10-year limited warranty
- Patent: [www.electricmirror.com/patents](http://www.electricmirror.com/patents)
- Made in America with U.S. and global components

#### AVAILABLE OPTIONS

- Ava™ Technology <sup>1, 2</sup>
- Keen™ Technology <sup>2</sup>
- Polaris™ Technology <sup>1, 2</sup>
- Seamless™ Technology <sup>1, 2</sup>
- Vive™ Technology <sup>1, 2</sup>
- Defogger
- CCT: 2,700K
- 0-10V dimming
- Forward-phase dimming
- 277V available <sup>3</sup>
- Custom sizes

#### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- Replaceable LEDs
- 60 initial lumens/inch
- Maximum 100 lumens/watt efficacy
- Calculated L<sub>70</sub> 52,000-hour LED lifespan

#### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

<sup>1</sup> Minimum order quantity required

<sup>2</sup> See technology specification sheets for more details

<sup>3</sup> May not be compatible with all upgrades and options

### INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

### MODELS

Base Model*	Dimensions	Power Requirements
NOV42-24.00x36.00-L7CSHD-30K	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	120/240 VAC, 38W
NOV42-30.00x36.00-L7CSHD-30K	30"W x 36"H x 1.75"D (762mm x 914mm x 44mm)	120/240 VAC, 43W
NOV42-36.00x36.00-L7CSHD-30K	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	120/240 VAC, 57W
NOV42-48.00x36.00-L7CSHD-30K	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	120/240 VAC, 75W
NOV42-60.00x36.00-L7CSHD-30K	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	120/240 VAC, 96W

\*Base model number shown only. To specify additional options, contact Electric Mirror at [sales@electricmirror.com](mailto:sales@electricmirror.com).

### DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

