



PRODUCT DESCRIPTION

Two beautiful frosted bands of luminescent LED lights are surrounded by a stylishly modern frame, creating a sublime Reflection™ that adds a distinct statement of prestige to your bedroom or bathroom.

SPECIFICATION STATEMENT

Solution shall consist of a framed, lighted mirror with forward-facing task lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using-replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 10-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- Title 24 compliance available
- 10-year limited warranty
- Patent: www.electricmirror.com/patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Ava™ Technology ^{1, 2}
- Keen™ Technology ²
- Polaris™ Technology ^{1, 2}
- Seamless™ Technology ^{1, 2}
- Vive™ Technology ^{1, 2}
- Defogger
- CCT: 2,700K
- 0-10V dimming
- Forward-phase dimming
- 277V available ³
- Urban Profile frame ebony finish standard; other finishes available
- Custom frames ¹
- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- Replaceable LEDs
- 50 initial lumens/inch
- Maximum 100 lumens/watt efficacy
- Calculated L₇₀ 124,000-hour LED lifespan

¹ Minimum order quantity required

² See technology specification sheets for more details

³ May not be compatible with all upgrades and options

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Power Requirements
REF2-MU11-29.00x41.00-L7CS-30K	29"W x 41"H x 2.13"D (737mm x 1041mm x 51mm)	120/240 VAC, 40W
REF2-MU11-41.00x41.00-L7CS-30K	41"W x 41"H x 2.13"D (1041mm x 1041mm x 51mm)	120/240 VAC, 40W
REF2-MU11-53.00x41.00-L7CS-30K	53"W x 41"H x 2.13"D (1346mm x 1041mm x 51mm)	120/240 VAC, 40W
REF2-MU11-65.00x41.00-L7CS-30K	65"W x 41"H x 2.13"D (1651mm x 1041mm x 51mm)	120/240 VAC, 40W

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

