Selah[™] Polycarbonate Lighted Mirror Product Specifications

ELECTRIC MIRROR®



PRODUCT DESCRIPTION

The gentle, serene lines of the Selah[™] invite you to take a peaceful pause. Constructed of impact-resistant polycarbonate and designed to meet the stringent requirements for behavioral health applications, this lighted mirror is well-suited for spaces where security and safety are essential.

SPECIFICATION STATEMENT

Solution shall consist of a polycarbonate, lighted mirror with forward-facing task lighting. Mirror shall have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 5-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S.-based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Impact-resistant polycarbonate mirror—IK10 rated
- Scratch-resistant coating
- Forward-facing task lighting
- Tamper-resistant hardware
- Suitable for damp locations
- IP65 rated*
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- Title 24 compliance available
- Accepted by NYS-OMH for behavioral health*
- 5-year limited warranty
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- CCT: 2,700K-6,500K
- 0-10V dimming
- Forward-phase dimming
- Custom sizes¹
- 277V available²

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,500K
- 50 initial lumens/inch
- Maximum 100 lumens/watt efficacy
- Calculated L₇₀ 124,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Ligature resistant

¹Minimum order quantity required

² May not be compatible with all upgrades and options



INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis to be recessed into wall and mounted to wall studs; mounting holes are provided
- Installation requires a bead of pick-proof silicone caulk (not included) installed around perimeter of mirror
- Controlled by non-dimming on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable
- Contact Electric Mirror for unique product installation and rough-in details

MODELS

Base Model**	Dimensions	Power Requirements
SEL-24.00x36.00-L7-35K***	24"W x 36"H x 2"D (610mm x 914mm x 51mm)	120/240 VAC, 37W
SEL-30.00x42.00-L7-35K	30"W x 42"H x 2"D (762mm x 1,067mm x 51mm)	120/240 VAC, 42W
SEL-36.00x36.00-L7-35K	36"W x 36"H x 2"D (914mm x 914mm x 51mm)	120/240 VAC, 37W
SEL-36.00x42.00-L7-35K	36"W x 42"H x 2"D (914mm x 1,067mm x 51mm)	120/240 VAC, 42W
SEL-48.00x36.00-L7-35K	48"W x 36"H x 2"D (1,219mm x 914mm x 51mm)	120/240 VAC, 37W

* IP65 rating and OMH acceptance requires a bead of pick-proof silicone caulk (not included) installed around perimeter of mirror

** Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com

*** Indicates specific model tested by NYS-OMH. Learn more: <u>https://omh.ny.gov/omhweb/patient_safety_standards/guide.pdf</u>

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)



