

HALO™ LIGHTED VANITY MIRROR
COMMERCIAL PRODUCT SPECIFIER



S T L V C

HAL4 - - - - -


MODEL CODE SIZE TECHNOLOGY OPTIONS LED TYPE VOLTAGE COLOR TEMP

ADDITIONAL NOTES ¹

S MIRROR SIZE

In box S, enter the code for the size of the mirror.

Size (DIA)	Code
Standard Mirror Sizes	
36" DIA	36.00
48" DIA	48.00
Custom ²	XX.XX



T TECHNOLOGY OPTIONS

In box T, enter the codes for each option with a hyphen in between each one.

Technology Options	Code
Ava™ Touch-Tunable White on Mirror ^{2, 3, 4, 5}	
▪ 1-Touch, 5 CCT Modes + Dimming	AH
▪ 1-Touch, 5 CCT Modes + Dim-to-Off + Memory	AK
Wiring (Hardwire Standard—No Code Needed)	
▪ 135° Offset Grounded Cord+Right-Angle Plug ⁵	CC2
Seamless™ LED Clock Technology ^{2, 3}	
▪ Hardwired Clock, Switched with Lights	CK2
Dimming Technology ⁴	
▪ 0-10V Dimming (120-277VAC)	D1
▪ Forward-Phase/Triac Dimming (120-277VAC)	D2
▪ Dali Dimming (120-277VAC)	D4
Defogger ⁵	
▪ Standard Defogger Pad	DF
Keen™ One-Touch Energy-Saving Technology ^{2, 3, 4}	
▪ 1-Touch, 5-Step Dimming, Off	KC

Indicates Standard Configuration

¹ Use the additional notes field to specify options not listed.

² Minimum order quantity required.

³ See technology specification sheets for more details.

⁴ Ava™ and Keen™ are not compatible with other dimming options.

⁵ May not be compatible with all upgrades and options.

L LED TYPE

In box L, enter the code for the LED type.

LED Type	Code
Standard Output (853 lumens/ft; 6.72 watts/ft)	LSERD
High Output ⁵ (1,280 lumens/ft; 9.72 watts/ft)	LHERD

V VOLTAGE

In box V, enter the code for the voltage (code N/A for 120VAC).


Voltage	Code
120VAC (Standard—Leave Code Blank)	
220—240VAC	230V
277VAC ⁵	277V

C COLOR TEMPERATURE

In box C, enter the code for the correlated color temperature.

CCT (90+ CRI)	Code
2,700K (90+ CRI)	27K
3,000K (90+ CRI)	30K
3,500K (90+ CRI)	35K
4,000K (90+ CRI)	40K
5,000K (90+ CRI)	50K





HALO™

PRODUCT DESCRIPTION

Bathe in the celestial aura of the Halo™ lighted mirror. Radiant wall-glow lighting creates a luminous ambiance, while the distinctive 3-inch clear area reveals the wallcovering behind the mirror, adding depth, dimension, and a striking floating effect. The result is a breathtaking statement piece that blends elegant illumination with modern design.

SPECIFICATION STATEMENT

Solution shall consist of a mirror using 480-hour CASS-tested, lead-free, copper-free, corrosion-resistant glass with wall-glow accent lighting around the perimeter, providing uniform light to the walls at all edges of the mirror. The product shall use dimmable, high-density (54 LEDs/foot), replaceable LED strips with 90+ CRI (Color Rendering Index) and delivering 1,280 initial lumens/foot with an efficacy of 130 lumens/watt. Product will be made in America with U.S. and global components and have a 10-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ✓ Global mirror technology leader for over 25 years
- ✓ More installations than all competitors combined
- ✓ Realistic warranty you can believe in and trust
- ✓ Lowest total cost of ownership
- ✓ U.S.-based customer service support
- ✓ 125,000-square-foot American manufacturing facility

LIGHTING FEATURES AND BENEFITS

- Industry-leading lumen output for better lighting
- Superior color rendering (CRI) for more natural, flattering, and softer light quality
- High-density linear LED design for even light distribution
- High-efficiency LEDs for best-in-class energy savings
- Perimeter wall-glow ambient lighting with diffuser for a finished side view

GENERAL FEATURES AND BENEFITS

- OmegaMirror™ corrosion-resistant, 480-hour CASS-tested proprietary mirror glass
- Environmentally-leading, lead-free, copper-free mirror glass composition
- Fast lead times
- Easy installation
- ADA compliant
- JA8-2022 compliant
- 10-year limited warranty
- Patent: www.electricmirror.com/patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Title 24 compliance ¹
- Ava™ touch-tunable white + dimming technology ^{2,3}
- Keen™ one-touch energy-saving dimming technology ^{2,3}
- Nightlight technology
- Seamless™ LED clock technology ^{2,3}
- Vive™ streaming audio technology ^{2,3}
- Defogger ⁴
- CCT: 2,700K / 3,000K / 3,500K / 4,000K / 5,000K ²
- 0-10V, phase/triac, or Dali dimming ^{2,4}
- 120VAC, 220–240VAC, or 277VAC power ^{2,4}
- Custom sizes ²

DEFAULT LIGHTING SPECIFICATIONS

- Best-in-class illumination: 1,280 initial lumens/foot
- Superior color rendering: 90+ CRI
- High-density design: 54 LEDs/foot
- High efficacy: 130 lumens/watt
- Color temperature (CCT): 3,000K
- LED L₇₀ Lifespan (calculated): 52,000-hours
- Extended longevity: replaceable LEDs


¹ Title 24 compliance requires 0-10V or forward-phase/triac dimming.

² Minimum order quantity required.

³ See technology specification sheets for more details.

⁴ May not be compatible with all upgrades and options.

DIMENSIONAL DRAWING (Not to scale.)



STANDARD MODELS

Model Number ^{1,4}	Dimensions ²	Initial Lumens/Fixture ³	LED Power Requirements ³
HAL4-36.00-LHERD-30K	36" DIA x 1.63" D (914mm DIA x 41mm D)	8,641	120-277VAC, 59W
HAL4-48.00-LHERD-30K	48" DIA x 1.63" D (1,219mm DIA x 41mm D)	12,695	120-277VAC, 77W

SAFETY & INSTALLATION SPECIFICATIONS (for Standard Models)

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror
- 120-277VAC hardwire electrical connection; provide 36" whip; junction box not required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by non-dimming on/off wall switch (by others)
- Installation wiring may be different on mirrors equipped with additional options

¹ Standard model numbers shown. For assistance specifying additional options, please contact Electric Mirror.

² Tolerances for dimensions are ±1/8" (±3mm).

³ Lumen output and power requirements are calculated based on component specifications and may vary from actual.

⁴ Specifications and dimensions are subject to change without notice. Electric Mirror reserves the right to change the part number specified based on the latest standards.